



Malli			MI2-56Q4DN1	MI2-71Q4DN1	MI2-80Q4DN1	MI2-90Q4DN1
Jäähdytysteho		kW	5,6	7,1	8,0	9,0
Lämmitysteho		kW	6,3	8,0	9,0	10,0
Sähkönkulutus	Jäähdytys	W	60	70	96	100
	Lämmitys	W	60	70	96	100
Äänitaso		dB(A)	35/34/31/31/30/28/26	35/35/34/31/30/28/27	36/35/34/31/31/29/28	37/35/34/31/31/30/28
Ilmamäärä		m <sup>3</sup> /h	893/866/804/744/714/698/635	977/937/864/800/778/738/671	1203/1131/1064/977/912/840/774	1349/1294/1230/1201/1111/1029/97
Mitat (LxKxS)	Kasetti	mm	840x230x840			840x300x840
	Paneeli	mm	950x70x950			
Paino (netto)	Kasetti/paneeli	kg	23,2/5,3			28,4/5,8
Putkiston mitta		tu	(3/8" + 5/8")			
Kylmäaine			R410A			
Kondenssiputki		mm	32			
Toimintarajat	Jäähdytys/lämmitys		17 ÷ 32/10 ÷ 30			
Sähköliitännät	Jännite	V/Ph/Hz	220-240/1/50			
	Virtakaapeli	mm <sup>2</sup>	3x1,5			
	Signaalikaapeli	mm <sup>2</sup>	3x0,75 (suojattu.)			

